

15

Topic: Oracle RDBMS Installation without using GWT.
(i.e in silent mode using Response file)

#date

37

```
# Unzip Software.ZIP in $ORACLE_HOME folder.  
# Cd /database/response  
# CP db_install.rsp /u01/app/oracle/  
# Cd /u01/app/oracle/  
# mv db_install.rsp db_install_oracle.rsp  
# Vi db_install_oracle.rsp  
  
oracle.install.option=INSTALL_DB_SWONLY  
ORACLE_HOSTNAME=nodes.localdomain  
INVENTORY_LOCATION=/u01/app/oraInventory  
SELECTED_LANGUAGES=CN  
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1  
ORACLE_BASE=/u01/app/oracle  
oracle.install.db.InstallEdition=EE  
oracle.install.db.isCustomInstall=true  
  
oracle..DBA_Group=dba  
oracle...OPER_Group=oinstall  
oracle...STARTUP_CENTRAL=BB_CONTROL  
SECURITY_UPDATES_VIA_MYORACLE=FALSE  
DECLINE_SECURITY_UPDATES=true
```

: wq.

```
#date  
# ls -l /u01/app/oracle/db-install-oracle.rsp  
# cd /opt/database  
# ./runInstaller -silent -responseFile /u01/app/oracle/  
db-install-oracle.rsp
```

Run the scripts as root user,

28

i.e #/u01/app/oraInventory/orainstRoot.sh

/u01/app/oracle/product/11.2.0/dbhome_1/root.sh

```
# cd /u01/app/oraInventory/logs (for checking successful  
# ls -l installation)
```

wc -l install.....log

tail install.....log

Edit Code is 0 (means successful).